

Portable Electrostatic Fieldmeter



Features:

- *Battery or line operation - AC power module included*
- *Two ranges: $\pm 2\text{kV/cm}$
 $\pm 20\text{kV/cm}$*
- *Remote probe for easy monitoring of hard-to-reach locations up to 1000 feet*
- *Chopper stabilizer for accurate measurements in ionized environments*
- *Recorder output for unattended monitoring*
- *Unequaled accuracy, stability and versatility*

Wherever you need non-contact static measurement

- Monitor charge buildup on webs during lamination, coating, manufacturing, printing
- Check bonding during bagging, dumping, transport operations
- Static surveys in offices, on production lines, "static-free" workstations
- Prevention of dendritic discharge patterns on photographic and X-ray film
- Loop control for consistency in electrostatic tacking of materials
- Monitor static levels in textile manufacturing to prevent shocks to personnel, bunching and flying of product
- Drift-free measurement in ionized environments



Specifications

Ranges: $\pm 2\text{kV/cm}$ and $\pm 20\text{kV/cm}$

Sensitivity: 1 V/cm and 10 V/cm, respectively

Static accuracy: Better than 5% of reading

Drift: $< 30\text{ V/cm/hour}$, non-cumulative after 30 minutes stabilization, referred to input

Noise: $< 10\text{ V/cm rms}$, 0 - 200 Hz referred to input

Response speed: 250 ms 10% to 90% (typical)

Analog output: $\pm 20\text{kV/cm} = \pm 2.0\text{V}$ output ($< 10\text{ ohm}$ impedance)

Batteries: Built-in, rechargeable, gel-type, 12V, 1.2AH, > 8 hours with backlight on charging system on-board, < 6 hours recharging time

AC power adapter: Power adapter supplied;
Input: 100 - 240 VAC/ 47 to 63 Hz/260mA

Dimensions: 10.5" x 6.5" x 2.6" (26.7 x 16.2 x 6.7 cm)

Weight: 2lbs., 6oz (1.1kg) w/batteries

Operating environment: 25°C , $\pm 10^{\circ}\text{C}$, 0-85% RH non-condensing, unaffected by ionized environment

Probe: 1036F-5, 1.75" dia. x 1.25 H (4.4 x 3.2cm) 8 oz (0.2kg) with 10 ft. (3m) cable

Probe Options: Any of our Model 1036 probes will work with the Model 257D. A full range of probe sensitivities and different case styles are available. Please refer to our Model 1036 literature. Optional cable lengths up to 1000 ft for remote operation are available.

Probe operating environment: -30°C to 100°C , non-condensing

Accessories Included: Power supply, connecting cable, manual, optional carrying case is available

Industry Approval

- Probe approved by Factory Mutual Research Corporation as intrinsically safe for use in Class I, Division 1, Groups C and D hazardous locations when used with approved IS barriers.
- ATEX approved sensors are available through Extronics at www.extronics.com
- CE Mark Compliant

Calibration

Factory calibrated prior to shipment. Recalibration should be performed annually, or more frequently if specified by contract or company policy. Your instrument should also be recalibrated any time it has been repaired or tampered with. We are happy to recalibrate your instrument for you at a reasonable cost, or provide information and procedures on calibration upon request.

Warranty

Each instrument and sub-assembly manufactured by them shall be free from defects in material and workmanship for a period of one year after shipment from the factory. This warranty is applicable to the original purchaser only.